



AC to DC OWL

FP-288



A member of the OWL family

Holiday OWL	FP-284
PoE OWL	FP-287
AC to DC OWL	FP-288
Step-Down OWL	FP-289

Provides Auxiliary DC Power for Streetlight Mounted Equipment



The AC to DC OWL provides DC power through a user specified cable and user specified connector for ancillary devices. The input power comes from a standard NEMA Street Light receptacle. Any line voltage up to 480 VAC is converted to user specified DC voltage.

Applications Include:

- WiFi/WiMax Radios
- Surveillance Cameras
- Traffic Monitoring
- Security Cameras
- Other communication and UPS systems

Specifications:

Input Voltage: 105 – 480 VAC

Output Voltage: 12 VDC, 24 VDC, 48 VDC, or User Specified Voltage

Connector: Power Link, Military Specification, Cat 5e, or User Specified

Cable Type: User Specified

Cable Length: User Specified

Housing: UV Stabilized, Impact Resistant, Gray Polycarbonate

ANSI Standard: Conforms to ANSI C136.10 and Proposed ANSI C136.35

Temperature Rating: -40 to +70C

Ordering Information:

Model # FP288 – Consult Factory

About FP Outdoor Lighting Controls

For more than 60 years FP OLC has been the largest global provider of photoelectric roadway lighting controls for the electric power industry. Our auxiliary power devices are universally accepted at conservative electric utilities and are the product of choice for streetlight mounted equipment manufacturers.

FP OLC is ready to help you power your future.